



US 20180309464A1

(19) **United States**

(12) **Patent Application Publication**
Mandegaran

(10) **Pub. No.: US 2018/0309464 A1**

(43) **Pub. Date: Oct. 25, 2018**

(54) **HYBRID-COUPLER-BASED RADIO FREQUENCY MULTIPLEXERS**

(52) **U.S. Cl.**

CPC **H04B 1/0057** (2013.01); **H04L 5/14** (2013.01); **H04B 1/52** (2013.01); **H04B 1/48** (2013.01)

(71) Applicant: **ABTUM INC.**, Irvine, CA (US)

(72) Inventor: **Sam Mandegaran**, Pasadena, CA (US)

(21) Appl. No.: **15/528,876**

(57) **ABSTRACT**

(22) PCT Filed: **Sep. 30, 2016**

(86) PCT No.: **PCT/US2016/054646**

§ 371 (c)(1),

(2) Date: **May 23, 2017**

Related U.S. Application Data

(60) Provisional application No. 62/240,229, filed on Oct. 12, 2015.

Publication Classification


(51) **Int. Cl.**

H04B 1/00 (2006.01)

H04B 1/48 (2006.01)

H04B 1/52 (2006.01)

A radio frequency (RF) multiplexer includes, for example, a common port, a first port for a first frequency band, a second port for a second frequency band, and a third port for a third frequency band. The RF multiplexer also includes, for example, a first quadrature hybrid coupler (QHC), a second QHC and a third QHC. A coupling of the first QHC, a first pair of filters, and the second QHC separates the first frequency band and the second frequency band from the common port to the first port and to the second port, respectively. A coupling of the first QHC, a second pair of filters, and the third QHC separates the first frequency band and the third frequency band from the common port to the first port and to the third port respectively.






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8




FIG. 9




FIG. 10




FIG. 11

1200a →




FIG. 12A

1200b →




FIG. 12B

1200c →




FIG. 12C

**HYBRID-COUPLER-BASED RADIO
FREQUENCY MULTIPLEXERS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS/INCORPORATION BY
REFERENCE**

[0001] This patent application makes reference to, claims priority to, and claims benefit from U.S. Provisional Application No. 62/240,229, filed on Oct. 12, 2015. The above-referenced application is hereby incorporated herein by reference in its entirety.

FIELD OF THE DISCLOSURE

[0002] Certain embodiments of the present disclosure relate to electromagnetic components, integrated circuits, and/or wireless communication devices and systems. More specifically, certain embodiments of the present disclosure relate to methods and systems that use hybrid-coupler-based radio frequency (RF) multiplexers.

BACKGROUND OF THE DISCLOSURE

[0003] Existing methods and systems for RF multiplexers can be costly, cumbersome and inefficient. Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with the present disclosure as set forth in the remainder of the present application with reference to the drawings.

BRIEF SUMMARY OF THE DISCLOSURE

[0004] Systems and/or methods that use hybrid-coupler-based radio frequency (RF) multiplexers, substantially as shown in and/or described in connection with at least one of the figures, as set forth more completely in the claims.

[0005] Various advantages, aspects and novel features of the present disclosure, as well as details of an illustrated embodiment thereof, will be more fully understood from the following description and drawings.

**BRIEF DESCRIPTION OF SEVERAL VIEWS OF
THE DRAWINGS**

[0006] The drawings are of illustrative embodiments. They do not illustrate all embodiments. Other embodiments may be used in addition or instead. Details that may be apparent or unnecessary may be omitted to save space or for more effective illustration. Some embodiments may be practiced with additional components or steps and/or without all of the components or steps that are illustrated.

[0007] FIG. 1A illustrates an embodiment of a duplexer according to the present disclosure that supports two frequency bands, where band 1 is centered at frequency f_1 , and band 2 is centered at frequency f_2 .

[0008] FIG. 1B illustrates an embodiment of a duplexer according to the present disclosure that supports two frequency bands, where band 1 is centered at frequency f_1 , and band 2 is centered at frequency f_2 .

[0009] FIG. 2 illustrates an embodiment of a duplexer according to the present disclosure used in a front-end of a frequency division duplexed wireless communication system.

[0010] FIG. 3 illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0011] FIG. 4A illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0012] FIG. 4B illustrates an embodiment of a multiplexer according to the present disclosure that supports four or more frequency bands.

[0013] FIG. 5A illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0014] FIG. 5B illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0015] FIG. 5C illustrates an embodiment of a multiplexer according to the present disclosure that supports four frequency bands.

[0016] FIG. 5D illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0017] FIG. 5E illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands.

[0018] FIG. 6 illustrates an embodiment of a multiplexer in support of four or more frequency bands.

[0019] FIG. 7A illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands with equalizers.

[0020] FIG. 7B illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands with equalizers and impedance matching networks.

[0021] FIG. 7C illustrates an embodiment of a multiplexer according to the present disclosure that supports three frequency bands with equalizers and impedance matching networks.

[0022] FIG. 7D illustrates another embodiment of a multiplexer according to the present disclosure that supports three frequency bands with equalizers and impedance matching networks.

[0023] FIG. 8 illustrates an embodiment of a multiplexer according to the present disclosure that supports five frequency bands.

[0024] FIG. 9 illustrates tunable multiplexer according to the present disclosure that supports three frequency bands.

[0025] FIG. 10 illustrates an exemplary application for an embodiment of a multiplexer according to the present disclosure that supports four frequency bands.

[0026] FIG. 11 illustrates an exemplary application for an embodiment of a multiplexer according to the present disclosure that supports four or more frequency bands.

[0027] FIG. 12A illustrates an embodiment of a frequency response of a multiplexer according to the present disclosure that supports three frequency bands.

[0028] FIG. 12B illustrates an embodiment of a frequency response of a multiplexer according to the present disclosure that supports four frequency bands.

[0029] FIG. 12C illustrates an embodiment of a frequency response of a multiplexer according to the present disclosure that supports five frequency bands.

DETAILED DESCRIPTION OF THE
DISCLOSURE

[0030] As utilized herein the terms “circuit” and “circuitry” refer to physical electronic components (i.e., hardware) and any software and/or firmware (“code”) which may configure the hardware, be executed by the hardware, and/or otherwise be associated with the hardware. As utilized herein, “and/or” means any one or more of the items in the list joined by “and/or”. As an example, “x and/or y” means any element of the three-element set $\{(x), (y), (x, y)\}$. As another example, “x, y, and/or z” means any element of the seven-element set $\{(x), (y), (z), (x, y), (x, z), (y, z), (x, y, z)\}$. As utilized herein, the term “exemplary” means serving as a non-limiting example, instance, or illustration. As utilized herein, the terms “e.g.” and “for example” set off lists of one or more non-limiting examples, instances, or illustrations.

[0031] The drawings are of illustrative embodiments. They do not illustrate all embodiments. Other embodiments may be used in addition or instead. Details that may be apparent or unnecessary may be omitted to save space or for more effective illustration. Some embodiments may be practiced with additional components or steps and/or without all of the components or steps that are illustrated.

[0032] Some embodiments according to the present disclosure contemplate that, in electronic communications, in order to correctly receive a desired signal, the desired signal is separated from many other signals that are present on the same medium. This is applicable to wired communication systems and/or wireless communication systems. In the case of wireless communication systems, for example, the task of separating the desired signal from other signals can be a substantial challenge since it might not be known what other signals are present in the air which may interfere with the receive circuitry. Further, the transmitter may also interfere with the receive circuitry since the transmitter sits on the same system as the receive circuitry and operates at a frequency very close to the desired receive frequency. There are many techniques to isolate a receiver from a transmitter.

[0033] Some embodiments according to the present disclosure contemplate using a duplexer, for example, and to achieve isolation between the transmitter and the receiver. An exemplary duplexer can use, for example, a pair of quadrature hybrid couplers (QHC) and filters for the desirable frequency bands.

[0034] As demand for higher bandwidths and better connectivity continues to grow, interest in carrier aggregation has increased. In carrier aggregation, a wireless device may receive the desired information at different frequency bands (or channels) and/or may transmit the information at different frequency bands (or channels).

[0035] In some embodiments of the present disclosure, a component that separates different frequencies or frequency bands is called a multiplexer. An RF multiplexer, in its simplest form, is a $1 \times N$ passive network including 1 nominal input and N nominal output ports (N is a positive integer) where each output corresponds to a specific frequency band. In other words, the transfer function from the input to each of the N outputs resembles a filter tuned to a specific frequency band. Furthermore, it is often desirable that the output ports of the multiplexer are isolated. In other words, the transfer functions from each of the output port to every other output port should have a small magnitude at the frequency bands corresponding to those two ports.

[0036] Some embodiments of the present disclosure provide $1 \times N$ RF multiplexers that include RF band-pass filters (BPF) with distinct passband frequencies that are connected to a common port using a passive network or a number of passive networks. The passive network or networks can ensure proper impedance at all frequency bands of interest and may assist in enhancing the frequency response.

[0037] In some embodiments of the present disclosure, an input port of an RF multiplexer may correspond to an antenna interface and the output ports may correspond to receive or transmit frequency bands.

[0038] In some embodiments of the present disclosure, a duplexer may be considered a multiplexer with $N=2$. In other words, a duplexer is a three-port device. A duplexer can be used, for example, in wireless communication systems supporting frequency division duplexing (FDD).

[0039] Some embodiments of the present disclosure contemplate that the requirements for RF filters and multiplexers have become more stringent in light of new communication standards where information channels and frequency bands are closer to each other; new communication devices such as smartphones where the footprint and cost of all components are getting smaller as more components are used in support of multiple standards and applications; and co-existing communication systems where multiple communication transmitters and receivers work simultaneously.

[0040] Some embodiments of the present disclosure contemplate that linearity, noise, and power handling requirements might lead to utilization of passive RF filters and multiplexers in many applications. The performance of passive RF filters may be limited by the quality factor (Q) of the components that are used in their realization. The filter selectivity as well as passband requirement may lead to a filter topology and filter order. For a given RF filter topology and order, insertion loss may reduce with the increase of component Q.

[0041] Some embodiments of the present disclosure contemplate various technologies can be used to realize passive RF filters and duplexers. For instance, capacitors, inductors, or transmission lines can be used to realize passive RF filters and duplexers. Electromagnetic resonators, including waveguide, air cavity, and dielectric (e.g., ceramic) resonators, can also be used to realize passive filters and duplexers. The quality factor of such components is proportional to their overall physical size. As such, it has been difficult to realize compact low-loss selective passive RF filters and duplexers using electromagnetic components and resonators.

[0042] In some embodiments of the present disclosure, piezoelectric material can be used to realize compact high-Q resonators. Surface acoustic wave (SAW) resonators can provide compact low-loss selective RF filters and duplexers. Bulk acoustic wave (BAW) resonators can also be used to construct high-performance RF filters and duplexers.

[0043] Micro-electro-mechanical system (MEMS) resonators with high quality factor can also be used in radio frequency filtering applications.

[0044] In some embodiments of the present disclosure, RF SAW filters and duplexers can be used in wireless communications such as cellular phones, wireless local area network (WLAN) transceivers, global positioning system (GPS) receivers, cordless phones, and so forth. RF SAW filters have been used as band-select filters, image-reject filters, intermediate frequency (IF) filters, transmitter noise or spur reduction filters, and so forth. A smartphone may

have several SAW resonators, SAW filters, and SAW multiplexers to support various communication systems and standards.

[0045] Some embodiments of the present disclosure provide resonators (e.g., BAW resonators) that have lower loss (or higher Q) or are more compact, especially at higher frequencies, compared with SAW resonators, for example. Therefore, RF filters and duplexers that use BAW resonators can have lower insertion loss, or higher selectivity, or smaller form factor compared with those that utilize SAW resonators, especially at higher frequencies. Thin film bulk acoustic resonators (FBAR) and bulk acoustic wave solidly mounted resonator (BAW SMR) are exemplary examples of BAW resonators.

[0046] In commercial systems, some embodiments of the present disclosure contemplate that the choice of technology may depend on the technical performance, such as power consumption as well as economic and business considerations such as cost, size, and time to market. For instance, while one technology may provide better performance compared with another technology, it might not be adopted for a commercial system that is cost sensitive. In the case of RF filters and duplexers, it may be desirable to use a technology that leads to the lower cost and/or more compact solution, as long as a predetermined performance criterion is met. In other words, a more expensive or larger solution might not be adopted, even if it provides better performance as compared with an alternative solution that meets an acceptable performance level at a lower cost and/or size. For instance, while RF filters and multiplexers that use BAW resonators may provide lower loss compared with RF filters and multiplexers that use SAW resonators for a given set of specifications, the higher relative cost of BAW technology, as well as its relatively smaller number of suppliers, might disfavor their usage in certain applications and standards. Other considerations may include, for example, the ease of integration with the rest of the components in a communication system. For instance, there may be performance, business, or economic advantages for integrating RF filters and multiplexers with low noise amplifiers (LNAs), power amplifiers (PAs), transmit/receive (T/R) or band-select switches, impedance matching networks, etc. A wireless communication device, such as a smartphone, can include a number of SAW filters and multiplexers as well as a number of BAW filters and duplexers. Each SAW filter or BAW filter or duplexer may be used for a specific communication application, standard, or frequency band.

[0047] Some embodiments of the present disclosure provide architectural solutions that enable realization of highly-selective, low-loss multiplexers with high-isolation between the ports. Some embodiments of the present disclosure use a lower cost or more compact technology within an innovative architecture that satisfies a comparable or better specification compared to what can be achieved using a more expensive or less compact technology. Exemplary embodiments might include replacing BAW multiplexers with SAW multiplexers using an innovative architecture, or replacing ceramic or cavity multiplexers with BAW multiplexers using an innovative architecture.

[0048] Some embodiments of the present disclosure provide architectural solutions that enable realization of tunable, reconfigurable, and/or programmable RF multiplexers that can satisfy the requirements of multi-standard communication systems.

[0049] Some embodiments of the present disclosure overcome technical difficulties related to using QHCs and filters as described in U.S. Pat. Nos. 3,453,638 and 4,029,902, which are incorporated by reference herein in their entirety. Some technical difficulties overcome by some embodiments of the present disclosure include, for example, incurring extra loss and non-idealities as additional sub-circuits are cascaded to support additional frequency bands, where the extra loss and non-idealities are based on, for example, the signal at some frequency bands traveling through several QHCs and being reflected from several filters before reaching a desired output.

[0050] Some embodiments of the present disclosure overcome technical difficulties related to using QHCs and filters in a tunable duplexer as described in U.S. Pat. No. 9,048,805, which is incorporated by reference herein in its entirety. Some technical difficulties overcome by some embodiments of the present disclosure include, for example, an extra QHC and an extra pair of filters on one side of the QHC and a single filter on the other side of the QHC to achieve carrier aggregation for three bands. Because the output of the antenna tuner is connected to two QHCs, impedance matching becomes a challenge if not impossible. Further, each one of the receive frequency bands is split into two. One half of that incoming signal never reaches the intended output and thus only half of the power of the incoming signal is usable.

[0051] In wireless communication, it can be desirable to receive and transmit, or operate at two frequency bands, at the same time using one antenna. To accomplish this, some embodiments of the present disclosure provide that circuitry is used to send most of the incoming signal from the antenna to the receiver, and send most of the outgoing signal from the transmitter to the antenna, while maintaining high isolation between the transmit and receive paths. Two circuitry options include circulators and/or duplexers.

[0052] Some embodiments of the present disclosure provide for receiving and transmitting simultaneously over more than two frequency bands. Just like the case for two frequency bands, it is desirable to have low insertion loss from and to the antenna for each frequency band while maintaining high isolation between frequency bands.

[0053] Some embodiments of the present disclosure provide a multiplexer for three or more frequency bands that are used concurrently. Some embodiments provide that QHCs and filters are used to separate multiple frequencies. An advantage of some embodiments is that some embodiments are modular and scalable in the number of frequency bands. Accordingly, more frequency bands can be supported without significant degradation in performance. Another advantage of some embodiments is that some embodiments enable low-cost, compact multiplexers for commercial wireless communication systems in support of carrier aggregation, multi-standard, multi-band, and multi-mode operation. Another advantage of some embodiments is that some embodiments enable low-cost compact tunable frequency multiplexers that meet the requirements of commercial wireless communication standards. Yet another advantage of some embodiments is that some embodiments relax the requirements for filters and associated components in a multiplexer.

[0054] FIG. 1A illustrates an exemplary duplexer 110 using two similar band-pass filters 105 and 106, and two QHCs 104 and 107. The signal at the common port 101 may contain information in frequency bands f_1 and f_2 . The

duplexer **110** separates this signal to two signals: a signal at port **102** that primarily includes the information at the f_2 frequency band, and a signal at port **109** that primarily includes the information at the f_1 frequency band. Ports **102** and **109** may be designated to receiver and/or transmit ports. Filters **105** and **106** pass signals in frequency band f_1 , but not in frequency band f_2 . In fact, filters **105** and **106** reflect the signal in frequency band f_2 at their inputs. A load **108**, usually but not always equal to the impedance of the other ports such as 50 Ohms, for example, is coupled to the QHC **107** for correct termination of an unused port of the QHC **107**. When designed properly, ports **102** and **109** are sufficiently isolated from each other, and the insertion loss at frequency band f_2 between ports **101** and **102** and the insertion loss at frequency band f_1 between ports **101** and **109** is sufficiently low.

[0055] FIG. 1B illustrates an exemplary duplexer **111** using three band-pass filters **103**, **105**, and **106** and two QHCs **104** and **107**. The operation of FIG. 1B is similar to that of FIG. 1A—the additional filter **103** for frequency band f_2 improves the isolation between ports **102** and **109**.

[0056] FIG. 2 illustrates an exemplary application of the circuitry in FIG. 1B in the front-end of a wireless communication system that supports FDD. The antenna **201** receives and transmits signals. Sub-circuit **211** is a duplexer. The duplexer **211** allows transmit signal (TX) to go from a power amplifier (PA) **202** at a transmitter output to an antenna **201** with little insertion loss, and receive signal (RX) to go from the antenna **201** to a low noise amplifier (LNA) **209** at a receiver input with little insertion loss, while keeping the receiver LNA **209** well isolated from the transmitter PA **202**. The component at the interface of the receiver with the duplexer **211** may be different from an LNA. Likewise, the component at the interface of the transmitter with the duplexer **211** may be different from a PA. The transmit signal that originates at the PA **202** goes through the TX filter **203** where most of the non-TX band frequencies are filtered out. The TX signal then goes through a QHC **204** where the TX signal is split into two signals that are 90° different in phase. The TX frequency band portion of the signals bounces back at the RX filters **205** and **206** because of the large impedance mismatch at the input ports of the RX filters **205** and **206** at the TX frequency band. The RX frequency band portion of the TX signal goes through the RX filters **205** and **206** and then through a QHC **207** where it constructively combines and is absorbed in a load **210**. The TX frequency band portion of the TX signal that is reflected off the RX filters **205**, **206** goes back through the QHC **204** and constructively combines at the antenna port of the QHC **204**. The incoming receive signal is received by the antenna **201** and enters the QHC **204**. The RX signal is split into two signals with a 90° phase difference between them. Both split signals go through the corresponding RX filters **205**, **206** and then enter the second QHC **207** where the signals are constructively combined at the upper right port of QHC **207** and then enter the LNA **209**. The isolation from the PA **202** to the LNA **209** is high since most of the TX signal goes to the antenna **201** and the portion that does not, for example, transmit noise in the RX frequencies, is mostly absorbed at the load **210**. A disadvantage of the circuitry in FIG. 2 is that it separates only two bands. As such, by itself, it cannot be used in communication systems supporting carrier aggregation.

[0057] FIG. 3 illustrates exemplary circuitry that extends the hybrid-based duplexer scheme of FIG. 1A to a multiplexer **300** supporting more frequency bands, such as three frequency bands. The multiplexer **300** is based, in part, on the duplexer architecture disclosed in U.S. Pat. No. 9,048, 805. There are several issues in this scheme. One issue arises from the interface between common port **311** and the two QHCs **307**, **308**. Since the common port **311** is connected to one 50-Ohm node of the QHC **307** and one 50-Ohm node of the QHC **308**, it is a challenge, if not impossible, to connect the common port **311** to a third node and to an antenna tuner **312** and still maintain an impedance match. This impedance mismatch will cause degradation in the signal. Another issue with this scheme is that the signal that is meant to go from the common port **311** to a port **309** will be split into two signals at the common port **311** and each of the two signals, which are now half the power of the original signal, goes through QHCs **307** and **308**. Only the signal that goes through QHC **307** ends up in the desired node **309** (through reflections from RF filters **303** and **304**) while the other half of the signal that goes through QHC **308** does not make it to port **309**. This means there is an inherent 3 dB loss for any signal going from the common port **311** to the output port **309**. For a similar reason, there is also a 3 dB loss for any signal going from the common port **311** to an output port **310**. The above-described issues are further exacerbated if the scheme were to be extended to support even more frequency bands.

[0058] FIG. 4A illustrates an exemplary application of the duplexer **110** of FIG. 1A to accommodate three frequency bands f_1 , f_2 , and f_3 . In this scheme, duplexers **403** and **404**, each based on the FIG. 1A scheme, are connected in cascade. The duplexer **404** separates frequency band f_1 at port **411** and sends frequency bands f_2 and f_3 to the duplexer **403**. The duplexer **403** separates frequency band f_2 at port **410** and frequency band f_3 at port **402**. One issue with this scheme is that frequency bands f_2 and f_3 travel through two duplexers and associated components prior to their separation at ports **410** and **402**. As such, signals at these frequency bands might incur more insertion loss and distortion. This might not be acceptable in many communication systems and standards.

[0059] FIG. 4B illustrates an exemplary application of the duplexer **110** of FIG. 1A to accommodate four or more frequency bands f_1 , f_2 , f_3 , f_4 , In this scheme, duplexers **404**, **403**, **414**, . . . , each based on the FIG. 1A scheme, are connected in cascade. The duplexer **404** separates frequency band f_1 at port **411** and sends frequency bands f_2 , f_3 , f_4 , . . . to the duplexer **403**. The duplexer **403** separates frequency band f_2 at port **410** and sends frequency bands f_3 , f_4 , . . . to the duplexer **414**. The duplexer **414** separates frequency band f_3 at port **417** and sends frequency bands f_4 , to another duplexer (not shown). In total, N-1 cascaded duplexers are used to separate N frequency bands. One issue with this scheme is that frequency bands must travel through several duplexers and associated components prior to their separation. As such, signals at these frequency bands might incur more insertion loss and distortion. For instance, frequency band f_4 travels through at least duplexers **404**, **403**, **414** before getting properly separated out. This might not be acceptable in many communication systems and standards.

[0060] FIG. 5A illustrates an embodiment of a multiplexer according to the present disclosure. Referring to FIG. 5A, a multiplexer **500a** is configured to cover three frequency

bands, and as such is also known as a triplexer. Coupling of a first pair of filters **507**, **508** (that are substantially similar) and a first QHC **504** and a second QHC **510**, by itself, discriminates frequency bands f_1 and f_2 . Coupling of a second pair of filters **505**, **506** (that are substantially similar) and the first QHC **504** and a third QHC **509**, by itself, discriminates frequency bands f_1 and f_3 . Together, judicious coupling of QHCs **504**, **509**, **510** and filters **505**, **506**, **507**, **508** enables discrimination of all frequency bands f_1 , f_2 , and f_3 of interest. The signal at the common port **501**, carrying signals at frequency bands f_1 , f_2 , and f_3 , is coupled to two nodes each having two filters, namely, the filters **505** and **507**, and the filters **506** and **508**, respectively, through the QHC **504**. The filters **505**, **506**, **507**, and **508** are designed to absorb all the signal power at their designated passbands while reflecting all the signal power at stopbands. For instance, the filters **505** and **506** absorb signals at frequency band f_3 , and reflect signals at frequency bands f_1 and f_2 . Likewise, filters **507** and **508** absorb signals at frequency band f_2 , and reflect signals at frequency bands f_1 and f_3 . Therefore, collectively, filters **505** and **507**, and filters **506** and **508**, reflect the signals at frequency band f_1 back to QHC **504** and port **502**.

[0061] In some embodiments, the impedance looking into a common node **519** of filters **505** and **507** is primarily determined by the filter **505** at frequency band f_3 and by the filter **507** at frequency band f_2 . The same holds for the impedance looking into a common node **520** of filters **506** and **508**. In practice, filters **505** and **507** are co-designed to ensure proper impedance level at their common node **519** while providing the desired frequency response. Filters **506** and **508** are co-designed to ensure proper impedance level at their common node **520** while providing the desired frequency response. In some embodiments, additional passive circuitry may be added at the common node of the filters to improve the impedance matching. One advantage of this scheme according to some embodiments is that information in each desired frequency band only travels through one pair of QHCs and appropriate filters, thereby eliminating the above-described extra insertion loss and distortion of other realizations. Filters **505**, **506**, **507**, **508** collectively reflect the portions of the common port signal that reside at frequency band f_1 back to the QHC **504** towards the first port **502**. Each of the first port **502**, the second port **513**, and the third port **511** may be an input port, an output port, or an input/output port. In other words, each of the ports **502**, **511**, and **513** may correspond to a transmitter port, a receiver port, or a transceiver port. The common port **501** may accommodate all three frequency bands f_1 , f_2 , and f_3 . In a wireless communication system, this common port **501** may correspond to an antenna port. In some embodiments, one or more of the filters **505**, **506**, **507**, **508** may have one or more passbands, and/or may specifically include one or more stopbands (notches) to eliminate undesired frequency bands.

[0062] FIG. 5B illustrates another embodiment of a multiplexer according to the present disclosure where an additional filter **503** with a passband at frequency band f_1 is added between port **502** of the scheme in FIG. 5A and Band 1 Port **522**. While the band discrimination operation of FIG. 5B is similar to that of FIG. 5A, the additional filter **503** filter improves the isolation between ports **522** and **511**, and the isolation between ports **522** and **513**. In some embodiments, filter **503** may have one or more passbands, and may

specifically include one or more stopbands (notches) to eliminate undesired frequency bands.

[0063] FIG. 5C illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 5C, a multiplexer **500c** is configured to cover four frequency bands, and as such is also known as a quadplexer. Filter **516**, with a passband frequency band f_4 , is added to the port **502** of the QHC **504**. Filters **503** and **516** are designed to absorb all the signal power at their designated passbands while reflecting all the signal power at stopbands. For instance, the filter **503** absorbs signals at frequency band f_1 and reflects signals at frequency band f_4 . Likewise, the filter **516** absorbs signals at frequency band f_4 , and reflects signals at frequency band f_1 . In some embodiments, the impedance looking into the common node **502** of the filters **503** and **516** is primarily determined by the filter **503** at frequency band f_1 and by the filter **516** at frequency band f_4 . In practice, filters **503** and **516** are co-designed to ensure proper impedance level at their common node **502** while providing the desired frequency response. In some embodiments, additional passive circuitry may be added at the common node **502** of these filters **503**, **516** to improve the impedance matching.

[0064] FIG. 5D illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 5D, a multiplexer **500d** (specifically a triplexer) includes, for example, circuitry block **503d**. Circuitry block **503d** is tuned to pass frequency band f_1 and stop frequency band f_2 (e.g., via a bandstop at frequency band f_2), and is added between the port **502** of the scheme in FIG. 5A and a Band 1 Port **523**. The circuitry block **503d** serves at least two purposes: it provides band-pass filtering at frequency band f_1 between ports **502** and **523**, and it provides a stopband filtering at frequency band f_2 between the ports **502** and **523**. As a result, the isolation between the port **523** for frequency band f_1 and the port **513** for frequency band f_2 is improved. In some embodiments, f_2 filter **517d** in the block **503d** may be the same or similar filter as the other f_2 filters **507** and **508**, or it may be a different filter that has a passband at frequency band f_2 . The filter **517d** does not strictly have to be a passband filter. For example, as long as the filter **517d** includes circuitry that passes frequency band f_2 and blocks frequency band f_1 , the circuitry may be used. In some embodiments, one or more of the filters **505**, **506**, **507**, **508**, and **515d** may have one or more passbands, and may specifically include one or more stopbands (notches) to eliminate undesired frequency bands.

[0065] FIG. 5E illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 5E, a multiplexer **500e** (specifically a triplexer) includes, for example, circuitry block **503e** tuned to pass frequency band f_1 , and stop frequency bands f_2 and f_3 (e.g., via a bandstop at frequency bands f_2 and f_3), and is added between port **502** of the scheme in FIG. 5A and a Band 1 Port **524**. The circuitry block **503e** serves at least two purposes: it provides band-pass filtering at frequency band f_1 between the ports **502** and **524**, and it provides stopband filtering at frequency bands f_2 and f_3 between the ports **502** and **524**. In some embodiments, the circuitry block **503e** includes f_1 filter (first filter) **515e**, f_2 filter (second filter) **517e**, f_3 filter (third filter) **518e**, and QHC (fourth QHC) **516e**. As a result, the isolation between the port **524** for frequency band f_1 and the port **513** for frequency band f_2 as well the isolation between the port **524** for frequency band

f_1 and the port **511** for frequency band f_3 is improved. In some embodiments, f_2 filter **517e** in the block **503e** may be the same or similar filter as the other f_2 filters **507** and **508**, or it may be a different filter that has a passband at frequency band f_2 . The filter **517e** does not strictly have to be a passband filter. For example, as long as the filter **517e** includes circuitry that passes frequency band f_2 and blocks frequency band f_1 , the circuitry may be used. In some embodiments, f_3 filter **518e** in the block **503e** may be the same or a similar filter as the other f_3 filters **505** and **506**, or it may be a different filter that has a passband at frequency band f_3 . The filter **518e** does not strictly have to be a passband filter. For example, as long as the filter **518e** includes circuitry that passes frequency band f_3 and blocks frequency band f_1 , the circuitry may be used. In some embodiments, one or more of the filters **505**, **506**, **507**, **508**, and **515e** may have one or more passbands, and may specifically include one or more stopbands (notches) to eliminate undesired frequency bands.

[0066] FIG. 6 illustrates one embodiment of a multiplexer according to the present disclosure. Referring to FIG. 6, a scalable multiplexer architecture **600** is configured to cover multiple frequency bands (e.g., four bands). For every new frequency band of interest, a pair of similar filters and a QHC can be added and connected to nodes **620** and **621**. Every similar filter pair, such as filters **609**, **610**, filters **607**, **608**, or filters **605**, **606**, passes one of the frequency bands of interest, such as frequency bands f_2 , f_3 , or f_4 , while not passing (reflecting) other frequency bands of interest. These filters need not be strictly band-pass filters with one passband. Filter **603** improves the isolation between port **602** and other ports, such as ports **618**, **616**, and **614**, at frequency band f_1 and the frequency bands f_2 , f_3 , and f_4 designated at those ports. The filter **603** need not be only a band-pass at frequency band f_1 , but may include one or more stopbands at other frequency bands to further enhance the isolation.

[0067] FIG. 7A illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 7A, multiplexer **700a** includes, for example, two pairs of equalizers **709**, **710** and **711**, **712** that are added to the scheme of FIG. 5B. These equalizers **709**, **710**, **711**, **712** may be used to compensate for the imperfections of the QHCs **704**, **713**, and **714** and filters **703**, **705**, **706**, **707**, and **708**. Each of these equalizers **709**, **710**, **711**, **712** may include, for example, a phase shifter and an attenuator. The phase shifter and the attenuator may be fixed or variable, depending on the application and design. One or more of the equalizers **709**, **710**, **711**, **712** may include one or more time delay elements, and may include one or more phase shifters and/or attenuators. In some embodiments, the equalizers **709**, **710**, **711**, **712** in the multiplexer **700a** may be fully passive (to ensure high linearity), low noise, and low power consumption. In some embodiments, the equalizers **709**, **710**, **711**, **712** in the multiplexer **700a** may include transmission lines with appropriate length and characterization impedance to enhance the isolation or reduce the insertion loss in presence of QHCs imperfections.

[0068] FIG. 7B illustrates another embodiment a multiplexer according to the present disclosure. Referring to FIG. 7B, multiplexer **700b** includes, for example, impedance matching networks **719** and **720** that are added to the scheme of FIG. 7A to compensate for unwanted impedance mismatches that may occur between f_3 filters **705**, **706** and QHC **704**. Although shown explicitly as separate circuitry blocks,

some embodiments provide that impedance matching networks **719**, **720** may be embedded in f_3 filters **705** and **706**, respectively.

[0069] FIG. 7C illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 7C, multiplexer **700c** includes, for example, impedance matching networks **721** and **722** that are added to the scheme of FIG. 7B to compensate for unwanted impedance mismatches that may occur between f_2 filters **707**, **708** and QHC **704**. Although shown explicitly as separate circuitry blocks, some embodiments provide that impedance matching networks **721**, **722** may be embedded in f_2 filters **707** and **708**, respectively.

[0070] FIG. 7D illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 7D, multiplexer **700d** provides, for example, that termination resistors **716** and **718** in FIG. 7C are replaced with tunable impedances **716d** and **718d**, respectively, to enhance the isolation between ports **717** (f_2) and **702** (f_1), and also between ports **715** (f_3) and **702** (f_1). In some embodiments, the values of the tunable impedances **716d** and **718d** may be set manually or automatically, and may depend on an antenna impedance. Tunable impedances **716d** and **718d** may include, for example, tunable capacitors, tunable inductors, tunable resistors, and/or tunable resonators.

[0071] FIG. 8 illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 8, multiplexer **800** is configured to accommodate five frequency bands, and is constructed from a cascade connection of triplexer **801** (based on the scheme of FIG. 5A) and triplexer **802** (based on the scheme of FIG. 5B). Other multiplexer configurations may also be constructed in a similar way by cascade connection of any number of multiplexers disclosed in the present disclosure.

[0072] FIG. 9 illustrates another embodiment of a multiplexer according to the present disclosure. Referring to FIG. 9, a tunable multiplexer, such as a tunable triplexer **900**, is configured to support three frequency bands that might not be fixed. To support frequency tunability, filters **903**, **905**, **906**, **907**, and **908** and QHCs **904**, **909**, and **910** may be tunable. Not all of these circuitry blocks must be tunable to realize a tunable multiplexer according to some embodiments of the present disclosure. In some embodiments, the QHCs **904**, **909**, and **910** may be wideband to support multiple frequency bands. Any number of mechanisms might be applied to enable tunability of the QHCs **904**, **909**, and **910**. The tunable filters **903**, **905**, **906**, **907**, and **908** may include tunable components such as tunable capacitors, tunable inductors, tunable resonators, etc. The control signals for the tunable circuitry blocks or components may be initiated from a transceiver or a processing unit or an algorithm, or may be set manually. Some embodiments of the tunable multiplexer may be realized using tunable circuitry blocks or components in any of the multiplexer structures or configurations of the present disclosure.

[0073] FIG. 10 illustrates an exemplary application of the present disclosure where a multiplexer, such as a quadplexer **1000**, is used in the front-end of a wireless communication system that supports FDD and receive carrier aggregation. In this exemplary application, frequency band f_1 is designated as transmit frequency band and frequency bands f_2 , f_3 , and f_4 are designated as receive frequency bands. A common port **1004** is connected to an antenna interface **1001** supporting

all four frequency bands. In some embodiments, the LNAs **1011**, **1012**, and **1013** are realized monolithically in one chip, or may be part of an integrated multi-band transceiver.

[0074] FIG. **11** illustrates another exemplary application of the present disclosure where a multiplexer **1100** is used in a front-end of a wireless communication system that supports FDD, receive carrier aggregation, and transmit carrier aggregation. In this exemplary application, frequency bands f_2 and f_4 are designated as transmit frequency bands and frequency bands f_1 and f_3 are designated as receive frequency bands. A common port **1104** is connected to an antenna interface **1101** supporting all four frequency bands. In some embodiments, LNA **1102** and LNA **1119** are realized monolithically in one chip, or may be part of an integrated multi-band transceiver.

[0075] FIG. **10** and FIG. **11** illustrate only two of the embodiments according to the present disclosure for which the multiplexers may be used in the front-end of a wireless communication system that supports FDD and/or carrier aggregation. Transmit and receive frequency bands may be designated to any of the multiplexer ports depending on the application. Various considerations may be considered in determining port designations such as insertion loss, power handling, linearity, and isolation.

[0076] FIG. **12A** illustrates a representative graph showing the frequency response of an embodiment of a multiplexer (e.g., a triplexer) according to the present disclosure that supports three frequency bands (e.g., an embodiment shown in FIG. **5A**). The graph **1200a** shows the S-parameters of an exemplary hybrid-coupler-based multiplexer realized using commercially available components. The solid lines correspond to the transfer functions from the common port to respective single band ports (e.g., in FIG. **5A**, from port **501** to ports **502**, **511**, and **513**). The dotted and dashed lines correspond to transfer functions between respective pairs of single band ports (e.g., in FIG. **5A**, pairs of ports **502**, **511**, and **513**). It can be seen that a low insertion loss (solid lines) and high port-to-port isolation (dotted and dashed lines) have been achieved.

[0077] FIG. **12B** illustrates a representative graph showing the frequency response of an embodiment of a multiplexer (e.g., a quadruplexer) according to the present disclosure that supports four frequency bands (e.g., an embodiment shown in FIG. **6**). The graph **1200b** shows the S-parameters of an exemplary hybrid-coupler-based multiplexer realized using commercially available components. The solid lines correspond to the transfer functions from the common port to respective single band ports. The dashed lines correspond to transfer functions between respective pairs of single band ports. It can be seen that a low insertion loss (solid lines) and high port-to-port isolation (dashed lines) have been achieved.

[0078] FIG. **12C** illustrates a representative graph showing the frequency response of an embodiment of a multiplexer according to the present disclosure that supports five bands (e.g., an embodiment shown in FIG. **8**). The graph **1200c** shows the S-parameters of the disclosed hybrid coupler based multiplexer realized using commercially available components. The solid lines correspond to the transfer functions from the common port to respective single band ports. The dashed lines correspond to transfer functions between respective pairs of single band ports. It can be seen that a low insertion loss (solid lines) and high port-to-port isolation (dashed lines) have been achieved.

[0079] In some embodiments, one or more of the QHCs in the RF multiplexers according to the present disclosure may be realized in an integrated passive device (IPD) technology, or in a low temperature co-fired ceramic (LTCC) technology, or on a printed circuit board (PCB). In some embodiments, one or more of the filters may be stacked over one or more of the QHCs.

[0080] Some embodiments of RF multiplexers according to the present disclosure may be used or included in hand portable devices supporting wireless communications such as, for example, a cellular phone, a mobile phone, a mobile cellular device, a mobile wireless communication device, a smartphone, a tablet, a laptop, a smartwatch, etc. Some embodiments of RF multiplexers according to the present disclosure may be used or included in devices supporting the wireless communication infrastructure such as base stations (including macro-, micro-, pico-, and femto-base stations), repeaters, etc. Some embodiments of RF multiplexers according to the present disclosure enable compact multi-band, multi-standard wireless communication devices, wireless communication devices that support carrier aggregation and FDD. Some embodiments of RF multiplexers according to the present disclosure enable multi-antenna wireless communication devices.

[0081] Other embodiments of the present disclosure may provide a non-transitory computer readable medium and/or storage medium, and/or a non-transitory machine readable medium and/or storage medium, having stored thereon, a machine code and/or a computer program having at least one code section executable by a machine and/or a computer, thereby causing the machine and/or computer to perform the steps as described herein for hybrid-coupler-based RF multiplexers.

[0082] Accordingly, aspects of the present disclosure may be realized in hardware, software, or a combination of hardware and software. The present disclosure may be realized in a centralized fashion in at least one computer system or in a distributed fashion where different elements are spread across several interconnected computer systems. Any kind of computer system or other apparatus adapted for carrying out the methods described herein is suited. A typical combination of hardware and software may be a general-purpose computer system with a computer program that, when being loaded and executed, controls the computer system such that it carries out the methods described herein.

[0083] Aspects of the present disclosure may also be embedded in a computer program product, which comprises all the features enabling the implementation of the methods described herein, and which when loaded in a computer system is able to carry out these methods. Computer program in the present context means any expression, in any language, code or notation, of a set of instructions intended to cause a system having an information processing capability to perform a particular function either directly or after either or both of the following: a) conversion to another language, code or notation; b) reproduction in a different material form.

[0084] While the present disclosure has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present disclosure. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without

departing from its scope. Therefore, it is intended that the present disclosure not be limited to the particular embodiment disclosed, but that the present disclosure will include all embodiments falling within the scope of the appended claims.

What is claimed is:

- 1. A radio frequency multiplexer, comprising:
 - a plurality of ports including a common port, a first port for a first frequency band, a second port for a second frequency band, and a third port for a third frequency band;
 - a plurality of quadrature hybrid couplers (QHCs) including a first QHC, a second QHC, and a third QHC; and
 - a plurality of pairs of filters including a first pair of filters and a second pair of filters, wherein:
 - the first pair of filters are coupled between the first QHC and the second QHC, and are configured to pass the second frequency band and not pass the first frequency band and the third frequency band,
 - the second pair of filters are coupled between the first QHC and the third QHC, and are configured to pass the third frequency band and not pass the first frequency band and the second frequency band,
 - the first QHC, the first pair of filters, and the second QHC are configured to separate the first frequency band from the common port to the first port, and separate the second frequency band from the common port to the second port, and
 - the first QHC, the second pair of filters, and the third QHC are configured to separate the first frequency band from the common port to the first port, and separate the third frequency band from the common port to the third port.
- 2. The radio frequency multiplexer of claim 1, comprising an additional filter coupled to the first port and configured to pass the first frequency band.
- 3. The radio frequency multiplexer of claim 1, comprising:
 - circuitry coupled to the first port, wherein:
 - the circuitry is configured to pass the first frequency band, but not pass the second frequency band, and not pass the third frequency band,
 - the circuitry includes a first filter tuned at the first frequency band, a fourth QHC, a second filter tuned at the second frequency band, and a third filter tuned at the third frequency band, and
 - the second filter and the third filter are coupled in parallel between two ports of the fourth QHC to generate band-stop responses at the second frequency band and the third frequency band.
- 4. The radio frequency multiplexer of claim 1, wherein more frequency bands are supported in a configuration that includes an additional QHC and an additional pair of filters for an additional frequency band, wherein:
 - the additional pair of filters are coupled to the same two ports of the first QHC to which the first pair of filters and the second pair of filters are coupled,
 - the additional pair of filters are configured to pass the additional frequency band, but do not pass remaining frequency bands, and

- the first QHC, the additional pair of filters, and the additional QHC are configured to separate the first frequency band from the common port to the first port, and separate the additional frequency band from the common port to the additional port.
- 5. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer includes one or more pairs of equalizers coupled to one or more of the pairs of filters.
- 6. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer includes one or more pairs of impedance matching networks coupled to one or more of the pairs of filters.
- 7. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer includes one or more tunable or variable impedances coupled to one or more of the QHCs.
- 8. The radio frequency multiplexer of claim 1, wherein one or more of the pairs of filters are tunable or reconfigurable.
- 9. The radio frequency multiplexer of claim 1, wherein one or more of the QHCs are tunable or reconfigurable.
- 10. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is configured to provide a cascade connection with one or more other radio frequency multiplexers to form a radio frequency multiplexer configuration.
- 11. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a front-end of a wireless communication system that supports carrier aggregation.
- 12. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a front-end of a wireless communication system that supports frequency division duplexing.
- 13. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a front-end of a multiband communication system.
- 14. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a hand portable device supporting wireless communication.
- 15. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a base station supporting a wireless communication infrastructure.
- 16. The radio frequency multiplexer of claim 1, wherein the radio frequency multiplexer is included in a repeater supporting a wireless communication infrastructure.
- 17. The radio frequency multiplexer of claim 1, wherein one or more of the filters include one or more of surface acoustic wave (SAW) filters and bulk acoustic wave (BAW) filters.
- 18. The radio frequency multiplexer of claim 1, wherein the first pair of filters and the second pair of filters are coupled to the same two ports of the first QHC.
- 19. The radio frequency multiplexer of claim 1, wherein one or more of the plurality of QHCs is realized in an integrated passive device (IPD) technology, or in a low temperature co-fired ceramic (LTCC) technology, or in a printed circuit board (PCB).
- 20. The radio frequency multiplexer of claim 1, wherein one or more filters of the plurality of pairs of filters are stacked over one or more QHCs of the plurality of QHCs.

* * * * *